

Product data sheet GEZE ActiveStop integrated



Door damper on both sides for interior wooden swing doors

AREAS OF APPLICATION

- ightarrow Right and left timber single-action doors indoors
- ightarrow Room doors with high access convenience
- ightarrow Single-action doors up to 1100 mm leaf width
- ightarrow Integrated installation in the door leaf
- ightarrow Barrier-free access in accordance with DIN 18040-2



PRODUCT FEATURES

- ightarrow Door opening angle with variable adjustment from 80°-140°
- ightarrow Can be used for right and left hand doors without conversion
- ightarrow Soft opening and closing of doors up to max. 45 kg leaf weight
- ightarrow Gentle stopping, quiet closing and comfortable keeping open of doors
- ightarrow Practically eliminates slamming doors, trapped fingers, and damage to walls and furniture
- ightarrow Secure holding of the door when open, meaning no door is stopper necessary
- ightarrow Opening and closing damping when installed can be set via a valve
- ightarrow Integrated safety valve offers overload protection

TECHNICAL DATA

Productname	GEZE ActiveStop integrated
Depth	28 mm
Height	64 mm
Leaf weight (max.)	45 kg
Leaf width (max.)	1100 mm
Category of door	flush-mounted, rebated
Leaf thickness from	38 mm
Identical design for DIN left and DIN right	Yes
Rebate space	approx. 6 mm clearance in handle area
Installation type	concealed
Adjustable draw-in damper	Yes, via valve
Draw-in damper in direction of closing movement from	25 °
Free swing area	25 ° - 60 °
Draw-in damper in direction of opening movement from	60 °
Adjustable door opening angle	Yes, stepless
Hold-open position adjustable	80 ° - 140 °
Safety valve againts overload	Yes

VARIANTS / ORDER INFO

Designation	Description	ldent- No.	Colour	Dimensions	Installation type
GEZE ActiveStop integrated	Door damper on both sides for interior wooden swing doors	163411	silver- coloured	286 x 32 x 45 x 28 mm	concealed

Product data sheet | Page 3 of 4 GEZE ActiveStop integrated



ACCESSORIES

MILLING EDGE COVER *

For covering the milling edge of rebated doors



Designation	Description	Ident-No.	Colour
Milling edge cover *	10 pieces, to cover the milling edge on rebated doors	169724	white RAL 9016
Milling edge cover *	10 pieces, to cover the milling edge on rebated doors	169725	grey RAL 7035
Milling edge cover	10 pieces, to cover the milling edge on rebated doors	170264	according to RAL

MILLING FIXTURE *

For milling door leaves and frames for the GEZE ActiveStop integrated



Designation	Description	Ident-No.
Milling fixture	For the processing of the door leaf and frame with a commercially available router; contains templates for guide rail and basic body milling for the GEZE ActiveStop integrated	166886

GUIDE RAIL FIXING PLATES

For fixing the concealed horizontally installed guide rail if there is insufficient screw depth



Designation	Description	Ident-No.
Fastening strips for guide rails	For fastening the integrated guide rail in the in timber frames with insufficient screw-in depth of fixing screws	165814

Product data sheet | Page 4 of 4 GEZE ActiveStop integrated



* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.