

Product data sheet

TSA 325 NT Manual *



Manual revolving door system for three- or four-leaf doors



AREAS OF APPLICATION

- Three- and four-leaf door systems
- Interior and exterior doors with low access frequency
- Representative building entrances with large incidence of light
- Façades with slim mullion-transom constructions
- Glass façades with the highest design standards
- Inner diameter ranging from 1800 to 3600 mm possible
- Suitable profile systems are fine-framed profile systems with ISO and mono glass, all-glass systems (GGS) and integrated all-glass systems (IGG)

PRODUCT FEATURES

- The door leaves can be activated by gently pushing them
- More cost-effective than automatic drives, since safety devices according to EN 16005 are no longer needed
- Precise closing of the door leaves with the side walls
- Effective insulation effect against draughts, weather and noise
- Optional speed limiter regulates the peripheral speed when reaching the max. limiting speed
- Optional automatic positioning device returns the door to its original position after a person has passed through it

TECHNICAL DATA

Productname	TSA 325 NT Manual *
Manual operation	Yes
With speed limiter (optional)	Yes
With positioning device (optional)	Yes
Servo function	Yes
Inner diameter (min.)	1800 mm
Inner diameter (max.)	3600 mm
For 3-leaf door systems	Yes
For 4-leaf door systems	Yes
Clear passage height	3000 mm
Canopy height (min.)	75 mm
Side elements version	10 mm LSG, 22 mm panel lining, 34 mm smooth-surface panel, Special glass on request
Version of roof structure	As dust protection roof with wood covering, optical sheet metal covering, waterproof roof with waterspout
Illumination	with roof variant
Floor covering	Entrance mat, Entrance mat according to customer wishes



Hot-air curtain system	Electric air curtain, hot water air curtain, possible, depends on the ceiling construction
Night-time closer layout	Inside, Outside
Night-time closer type	Manual, Automatic
Night-time closer design	10 mm LSG, 22 mm ISO glass, 22 mm panel lining, Special glass on request
Lock	Manual, Rod, electromechanical
Door handles horizontal or vertical	Yes
Floor ring	Yes
Underfloor operator	Yes
Disabled person's button	Yes
Standard conformity	DIN 18650, EN 16005

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.